

## TYRES

Product group	Tyres
Item number	15726470
Valid tyre size	520 / 85 R 46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp  
Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

## Technical Informations

Item number	15726470
EAN	8903094030569
Valid tyre size	520 / 85 R 46
Alternative size 1	20.8R46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	226,42
Recommended rim size	DW16L
Permitted rim size	DW18L, W18L, W18A
Maximum air pressure [bar].	1,60
Section width (mm)	516
Outer diameter of tyre [mm].	2052
Stat. radius (SLR) [mm]	949
Rolling circumference [mm].	6157
Tread depth (mm)	56,5
Number of lugs	24x2
Tyre capacity 75% [ltr.]	594
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		1,60	
158 B	4250	50		1,60	