

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15726472       |
| Valid tyre size | 520 / 85 R 46  |
| LI / SI / PR    | 173 A8 / 173 B |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Agrimax RT 855 |



Bohnenkamp  
Moving Professionals



## Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

**Technical Informations**

|                              |                   |
|------------------------------|-------------------|
| Item number                  | 15726472          |
| EAN                          | 8903094040544     |
| Valid tyre size              | 520 / 85 R 46     |
| Alternative size 1           | 20.8R46           |
| LI / SI / PR                 | 173 A8 / 173 B    |
| TL/TT                        | TL                |
| Brand                        | BKT               |
| Tread pattern                | Agrimax RT 855    |
| Antistatic                   | No                |
| Tyre colour                  | Black             |
| ECE regulation number        | ECE 106           |
| Nettogewicht [kg] (gültig)   | 241.03            |
| Recommended rim size         | DW16L             |
| Permitted rim size           | DW18L, W18L, W18A |
| Maximum air pressure [bar].  | 4,00              |
| Section width (mm)           | 516               |
| Outer diameter of tyre [mm]. | 2052              |
| Stat. radius (SLR) [mm]      | 964               |
| Speed Radius Index (SRI)     | 975               |
| Rolling circumference [mm].  | 6310              |
| Tread depth (mm)             | 56,5              |
| Number of lugs               | 24x2              |
| Tyre capacity 75% [ltr.]     | 594               |
| E-Ready                      | No                |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 173 A8 | 6500               | 40           |               | 4,00                     |              |
| 173 B  | 6500               | 50           |               | 4,00                     |              |