

TYRES

Product group	Tyres
Item number	15726480
Valid tyre size	480 / 80 R 50
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Standard tyre of the 85 series for tractors in the medium-power range up to 180 hp.
- Large choice of dimensions, may also be used as a row crop tyre.
- Good traction and self-cleaning.
- Rounded lugs in the shoulder area for plant protection.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726480
EAN	8903094029914
Valid tyre size	480 / 80 R 50
Alternative size 1	18.4R50
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	214,89
Recommended rim size	DW16A
Permitted rim size	DW15A, W15A
Maximum air pressure [bar].	2,40
Section width (mm)	489
Outer diameter of tyre [mm].	2036
Stat. radius (SLR) [mm]	941
Rolling circumference [mm].	6183
Tread depth (mm)	54,0
Number of lugs	25x2
Tyre capacity 75% [ltr.]	498.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		2,40	
159 B	4375	50		2,40	