

## TYRES

Product group	Tyres
Item number	15726660
Valid tyre size	620 / 75 R 26 CHO
LI / SI / PR	166 A8 / 166 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris



## Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

## Technical Informations

Item number	15726660
EAN	8903094035809
Valid tyre size	620 / 75 R 26 CHO
LI / SI / PR	166 A8 / 166 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	203,00
Recommended rim size	DW20B
Maximum air pressure [bar].	3,20
Section width (mm)	625
Tread width (mm)	560
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	730
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4851
Tread depth (mm)	50,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	542.25
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		3,20	
166 B	5300	50		3,20	