

TYRES

Product group	Tyres
Item number	15726790
Valid tyre size	600 / 70 R 30
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Fortis



Notes and features

- Super wide tyres for high performance tractors from about 200 hp.
- High load capacities paired with excellent traction, due to extended contact area and solid lugs.
- Efficient in agricultural use and increased transport performance with high ride comfort and lower rolling resistance.
- Reduction of operating costs through fuel savings and high mileage.



Technical Informations

Item number	15726790
EAN	8903094032952
Valid tyre size	600 / 70 R 30
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Fortis
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	181,94
Recommended rim size	DW20B
Permitted rim size	DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	611
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	724
Rolling circumference [mm].	4810
Tread depth (mm)	58,0
Number of lugs	18x2
Lug width (mm)	43
Tyre capacity 75% [ltr.]	489
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		2,40	
158 D	4250	65		2,40	