

TYRES

Product group	Tyres
Item number	15726941
Valid tyre size	580 / 70 R 38
LI / SI / PR	155 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726941
EAN	8903094062249
Valid tyre size	580 / 70 R 38
LI / SI / PR	155 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	205,94
Recommended rim size	W18L
Permitted rim size	DW20B
Maximum air pressure [bar].	1,60
Section width (mm)	577
Outer diameter of tyre [mm].	1827
Stat. radius (SLR) [mm]	821
Rolling circumference [mm].	5505
Tread depth (mm)	57,5
Number of lugs	20x2
Lug width (mm)	46
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 D	3875	65		1,60	