

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15726946 |
| Valid tyre size | 650 / 75 R 38 |
| LI / SI / PR | 169 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15726946 |
| EAN | 8903094063895 |
| Valid tyre size | 650 / 75 R 38 |
| LI / SI / PR | 169 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 765 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 252,56 |
| Recommended rim size | DW21B |
| Permitted rim size | DW20B, DW23B |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 655 |
| Outer diameter of tyre [mm]. | 1941 |
| Stat. radius (SLR) [mm] | 874 |
| Rolling circumference [mm]. | 5820 |
| Tread depth (mm) | 58,0 |
| Number of lugs | 20x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 D | 5800 | 65 | | 2,40 | |