

TYRES

Product group	Tyres
Item number	15726946
Valid tyre size	650 / 75 R 38
LI / SI / PR	169 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
 - Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
 - Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726946
EAN	8903094063895
Valid tyre size	650 / 75 R 38
LI / SI / PR	169 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	252,56
Recommended rim size	DW21B
Permitted rim size	DW20B, DW23B
Maximum air pressure [bar].	2,40
Section width (mm)	655
Outer diameter of tyre [mm].	1941
Stat. radius (SLR) [mm]	874
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5820
Tread depth (mm)	58,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		2,40	