

TYRES

Product group	Tyres
Item number	15726961
Valid tyre size	710 / 70 R 38
LI / SI / PR	166 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765M



Notes and features

- The BKT Agrimax RT 765M is a 70 series radial tyre for tillage, field and transport use, grape harvesting and other applications.
- Its large contact area provides very good traction with low soil compaction.
- The tyre is characterised by very good self-cleaning properties.

Technical Informations

Item number	15726961
EAN	8903094066773
Valid tyre size	710 / 70 R 38
LI / SI / PR	166 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	284,48
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	1,60
Section width (mm)	716
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	859
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5751
Tread depth (mm)	58,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		1,60	