

TYRES

Product group	Tyres
Item number	15726985
Valid tyre size	650 / 75 R 42
LI / SI / PR	170 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	15726985
EAN	8903094065493
Valid tyre size	650 / 75 R 42
LI / SI / PR	170 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	272,66
Recommended rim size	DW21B
Permitted rim size	DW20B, DW23B
Maximum air pressure [bar].	2,40
Section width (mm)	655
Outer diameter of tyre [mm].	2043
Stat. radius (SLR) [mm]	916
Rolling circumference [mm].	6147
Tread depth (mm)	58,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 D	6000	65		2,40	