

TYRES

Product group	Tyres
Item number	15727105
Valid tyre size	540 / 65 R 28
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

Technical Informations

Item number	15727105
EAN	8903094053704
Valid tyre size	540 / 65 R 28
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	118,80
Recommended rim size	W16L
Permitted rim size	W18L
Maximum air pressure [bar].	1,60
Section width (mm)	530
Tread width (mm)	490
Outer diameter of tyre [mm].	1413
Stat. radius (SLR) [mm]	642
Rolling circumference [mm].	4202
Tread depth (mm)	48,0
Number of lugs	20x2
Lug width (mm)	40
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		1,60	
142 D	2650	65		1,60	