Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15727120	
Valid tyre size	540 / 65 R 30	
LI / SI / PR	153 A8 / 150 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax RT 657	





Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15727120
EAN	8903094029150
Valid tyre size	540 / 65 R 30
LI / SI / PR	153 A8 / 150 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	131,63
Recommended rim size	W16L
Permitted rim size	W18L
Maximum air pressure [bar].	2,40
Section width (mm)	530
Tread width (mm)	510
Outer diameter of tyre [mm].	1464
Stat. radius (SLR) [mm]	670
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4403
Tread depth (mm)	50,0
Number of lugs	20x2
E-Ready	No

14.03.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		2,40	
150 D	3350	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.