

## TYRES

Product group	Tyres
Item number	15727132
Valid tyre size	650 / 75 R 32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



## Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

## Technical Informations

Item number	15727132
EAN	8903094055968
Valid tyre size	650 / 75 R 32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	232,94
Recommended rim size	DW21B
Permitted rim size	DW20B, DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	655
Tread width (mm)	590
Outer diameter of tyre [mm].	1789
Stat. radius (SLR) [mm]	807
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5416
Tread depth (mm)	49,5
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		3,20	
172 B	6300	50		3,20	