

## TYRES

Product group	Tyres
Item number	15727154
Valid tyre size	VF 710 / 60 R 34 NRO
LI / SI / PR	173 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax V-Flecto



## Notes and features

- The BKT Agrimax V-Flecto is a VF tyre of the new generation.
- Compared with a standard tyre, the tyre achieves 40% more load capacity at the same inflation pressure or the same load capacity with 40% less inflation pressure.
- In contrast to most VF tyres, the tyre can be mounted on a standard rim (NRO=Narrow Rim Option).
- Its 10 % larger contact area compared with a standard tyre enables outstanding traction while significantly reducing soil compaction.
- The specially shaped bead (Bead Protection System) closes extremely airtight and keeps the inflation pressure constant in all conditions.
- During road journeys, the particular lug angles ensure reduced vibrations and noise levels.
- There is no need to adjust the inflation pressure for optimum performance both in the field and on the road
- The extremely strong casing provides a 10 % longer service life in comparison with a standard tyre, even in difficult conditions.

## Technical Informations

Item number	15727154
EAN	8903094069507
Valid tyre size	VF 710 / 60 R 34 NRO
LI / SI / PR	173 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax V-Flecto
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	241,57
Recommended rim size	DW25B
Permitted rim size	DW24B, DW27B, DW23B(NRO)
Maximum air pressure [bar].	2,00
Section width (mm)	708
Tread width (mm)	690
Outer diameter of tyre [mm].	1716
Stat. radius (SLR) [mm]	752
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5097
Tread depth (mm)	61,5
Number of lugs	19x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		2,00	