

TYRES

Product group	Tyres
Item number	15727197
Valid tyre size	710 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600





Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.



Technical Informations

Item number	15727197
EAN	8903094063420
Valid tyre size	710 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	261,77
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	3,20
Section width (mm)	706
Tread width (mm)	630
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	881
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5926
Tread depth (mm)	48,0
Number of lugs	23x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		3,20	
178 D	7500	65		3,20	