

## TYRES

Product group	Tyres
Item number	15727445
Valid tyre size	230 / 95 R 32
LI / SI / PR	128 A8 / 128 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



## Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

**Technical Informations**

<b>Item number</b>	15727445
<b>EAN</b>	8903094026678
<b>Valid tyre size</b>	230 / 95 R 32
<b>Alternative size 1</b>	9.5R32
<b>LI / SI / PR</b>	128 A8 / 128 B
<b>TL/TT</b>	TL
<b>Brand</b>	BKT
<b>Tread pattern</b>	Agrimax RT 955
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	45,61
<b>Recommended rim size</b>	W8
<b>Permitted rim size</b>	W7
<b>Maximum air pressure [bar].</b>	4,00
<b>Section width (mm)</b>	238
<b>Outer diameter of tyre [mm].</b>	1251
<b>Stat. radius (SLR) [mm]</b>	585
<b>Rolling circumference [mm].</b>	3810
<b>Tread depth (mm)</b>	33,0
<b>Number of lugs</b>	27x2
<b>Lug width (mm)</b>	23
<b>E-Ready</b>	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A8	1800	40		4,00	
128 B	1800	50		4,00	