Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15727460
Valid tyre size	230 / 95 R 36
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

GROWING TOGETHER

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15727460
EAN	8903094027477
Valid tyre size	230 / 95 R 36
Alternative size 1	9.5R36
LI / SI / PR	130 A8 / 130 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	48,50
Recommended rim size	W8
Permitted rim size	W7
Maximum air pressure [bar].	4,00
Section width (mm)	238
Outer diameter of tyre [mm].	1352
Stat. radius (SLR) [mm]	639
Rolling circumference [mm].	4112
Tread depth (mm)	33,0
Number of lugs	29x2
Lug width (mm)	23
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 A8	1900	40		4,00	
130 B	1900	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.