

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15727580 |
| Valid tyre size | 380 / 90 R 46 |
| LI / SI / PR | 159 A8 / 159 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 945 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15727580 |
| EAN | 8903094021833 |
| Valid tyre size | 380 / 90 R 46 |
| Alternative size 1 | 14.9R46 |
| LI / SI / PR | 159 A8 / 159 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 945 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 139,45 |
| Recommended rim size | W12 |
| Permitted rim size | W11, W13 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 380 |
| Outer diameter of tyre [mm]. | 1852 |
| Stat. radius (SLR) [mm] | 859 |
| Rolling circumference [mm]. | 5699 |
| Tread depth (mm) | 46,0 |
| Number of lugs | 28x2 |
| Lug width (mm) | 33 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 159 A8 | 4375 | 40 | | 4,00 | |
| 159 B | 4375 | 50 | | 4,00 | |