

TYRES

Product group	Tyres
Item number	15727580
Valid tyre size	380 / 90 R 46
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727580
EAN	8903094021833
Valid tyre size	380 / 90 R 46
Alternative size 1	14.9R46
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	139,45
Recommended rim size	W12
Permitted rim size	W11, W13
Maximum air pressure [bar].	4,00
Section width (mm)	380
Outer diameter of tyre [mm].	1852
Stat. radius (SLR) [mm]	859
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5699
Tread depth (mm)	46,0
Number of lugs	28x2
Lug width (mm)	33
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	