

TYRES

Product group	Tyres
Item number	15727641
Valid tyre size	380 / 90 R 50
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727641
EAN	8903094065479
Valid tyre size	380 / 90 R 50
Alternative size 1	14.9R50
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	155,73
Recommended rim size	W12
Permitted rim size	W11, W13
Maximum air pressure [bar].	4,00
Section width (mm)	390
Outer diameter of tyre [mm].	1954
Stat. radius (SLR) [mm]	921
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5958
Number of lugs	30x2
Lug width (mm)	46
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		4,00	
160 B	4500	50		4,00	