

TYRES

Product group	Tyres
Item number	15727645
Valid tyre size	VF 380 / 105 R 50
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	15727645
EAN	8903094048113
Valid tyre size	VF 380 / 105 R 50
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	206,90
Recommended rim size	DW13
Permitted rim size	TW13, W13, W12
Maximum air pressure [bar].	4,40
Section width (mm)	400
Tread width (mm)	345
Outer diameter of tyre [mm].	2050
Stat. radius (SLR) [mm]	934
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6211
Tread depth (mm)	46,0
Number of lugs	36x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		4,40	