

## TYRES

Product group	Tyres
Item number	15727731
Valid tyre size	320 / 90 R 54
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

## Technical Informations

Item number	15727731
EAN	8903094037094
Valid tyre size	320 / 90 R 54
Alternative size 1	12.4R54
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	123,65
Recommended rim size	W10
Permitted rim size	W9, W11
Maximum air pressure [bar].	4,40
Section width (mm)	319
Outer diameter of tyre [mm].	1948
Stat. radius (SLR) [mm]	930
Rolling circumference [mm].	6021
Tread depth (mm)	43,0
Number of lugs	36x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		4,40	
156 B	4000	50		4,40	