

TYRES

Product group	Tyres
Item number	15735214
Valid tyre size	340 / 80 R 18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 529



Notes and features

- The BKT Multimax MP 529 is a radial tyre for small wheel loaders and municipal tractors in excavating and loading operations.
- Its distinctive tread pattern design provides very good traction in all usage conditions.
- The strong cut and puncture-resistant rubber compound guarantees a long service life, even when used on hard and abrasive surfaces.
- Thanks to the strong carcass, the tyre provides stability, high loading capacities and puncture resistance.

Technical Informations

Item number	15735214
EAN	8903094054305
Valid tyre size	340 / 80 R 18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 529
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	58,23
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	4,00
Section width (mm)	343
Outer diameter of tyre [mm].	1001
Stat. radius (SLR) [mm]	445
Speed Radius Index (SRI)	475
Rolling circumference [mm].	3007
Tread depth (mm)	28,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	50		4,00	
143 B	2725	40		4,00	