

TYRES

Product group	Tyres
Item number	15735215
Valid tyre size	360 / 70 R 18
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

Technical Informations

Item number	15735215
EAN	8903094053650
Valid tyre size	360 / 70 R 18
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,76
Recommended rim size	11
Permitted rim size	W10SDC, W11, 12, 12SDC
Maximum air pressure [bar].	4,00
Section width (mm)	360
Outer diameter of tyre [mm].	969
Stat. radius (SLR) [mm]	439
Speed Radius Index (SRI)	475
Rolling circumference [mm].	2887
Tread depth (mm)	27,5
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		4,00	
142 B	2650	50		4,00	