

TYRES

Product group	Tyres
Item number	15735224
Valid tyre size	340 / 80 R 20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

Technical Informations

Item number	15735224
EAN	8903094053452
Valid tyre size	340 / 80 R 20
LI / SI / PR	144 A8 / 144 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,30
Recommended rim size	11
Permitted rim size	W10, 11SDC, W11, 12, 12SDC
Maximum air pressure [bar].	4,00
Section width (mm)	343
Outer diameter of tyre [mm].	1052
Stat. radius (SLR) [mm]	483
Speed Radius Index (SRI)	500
Rolling circumference [mm].	3176
Tread depth (mm)	27,0
Number of lugs	30x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,00	
144 B	2800	50		4,00	