

## TYRES

Product group	Tyres
Item number	15735229
Valid tyre size	400 / 70 R 20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



## Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

## Technical Informations

Item number	15735229
EAN	8903094052073
Valid tyre size	400 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	75,30
Recommended rim size	13
Permitted rim size	12SDC, 13SDC, 14
Maximum air pressure [bar].	4,00
Section width (mm)	404
Outer diameter of tyre [mm].	1068
Stat. radius (SLR) [mm]	494
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3282
Tread depth (mm)	28,5
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	50		4,00	
149 B	3250	40		4,00	