

TYRES

Product group	Tyres	
Item number	15735233	
Valid tyre size	405 / 70 R 20	
LI / SI / PR	155 A2 / 151 A4	
TL/TT	TL	
Brand	BKT	
Tread pattern	BK Loader 53	



Notes and features

- The BK-Loader 53 is a tyre for loaders in industrial and heavy transport use, particularly recycling
- Its extremely deep tread pattern and rubber compound tailored to the application ensure slow tread wear e.g. on concrete slabs, and resistance to cuts and punctures
- Its specially designed aramid belt reliably protects the tyre against damages
- The special tread pattern design provides excellent lateral stability in harsh conditions
- Additionally, the tyre has excellent self-cleaning properties and good grip on wet and dry surfaces due to this tread pattern



Technical Informations

Item number	15735233
EAN	8903094054428
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 151 A4
TL/TT	TL
Brand	ВКТ
Tread pattern	BK Loader 53
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	122,60
Recommended rim size	13
Permitted rim size	14, 13SDC, 12, 12SDC
Maximum air pressure [bar].	5,50
Section width (mm)	407
Outer diameter of tyre [mm].	1097
Stat. radius (SLR) [mm]	511
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3339
Tread depth (mm)	56,5
Number of lugs	20x2
E-Ready	No



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A2	3875	10		5,50	
151 A4	3450	20		5,50	