

## TYRES

Product group	Tyres
Item number	15735239
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



## Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

## Technical Informations

Item number	15735239
EAN	8903094052097
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	112,00
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	465
Outer diameter of tyre [mm].	1254
Stat. radius (SLR) [mm]	574
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3801
Tread depth (mm)	32,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	50		4,00	
159 B	4375	40		4,00	