

TYRES

Product group	Tyres
Item number	15735358
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

Technical Informations

Item number	15735358
EAN	8903094052714
Valid tyre size	440 / 80 R 28
LI / SI / PR	156 A8 / 156 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	130,50
Recommended rim size	DW14L
Permitted rim size	DW13, DW13L, DW15L
Maximum air pressure [bar].	3,20
Section width (mm)	441
Outer diameter of tyre [mm].	1415
Stat. radius (SLR) [mm]	648
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4270
Tread depth (mm)	34,5
Number of lugs	30x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	50		3,20	
156 B	4000	40		3,20	