

TYRES

Product group	Tyres
Item number	15775230
Valid tyre size	650 / 65 R 38
LI / SI / PR	175 A8 / 170 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 697



Bohnenkamp
Moving Professionals



Notes and features

- The Ridemax IT 697 (M+S) is a municipal tyre suitable for various applications.
- It is particularly suitable for state-of-the-art contractors in winter operations.
- The tyre offers excellent grip in the field on snow and ice, even without snow chains.
- Thanks to its special tread pattern with sipes and its rubber compound, the tyre ensures full stability, comfort and safety in difficult, wintry road conditions.
- The strong casing ensures durability and a long service life.

Technical Informations

Item number	15775230
EAN	8903094055418
Valid tyre size	650 / 65 R 38
LI / SI / PR	175 A8 / 170 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 697
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	228,87
Recommended rim size	DW20B
Permitted rim size	DW18L
Maximum air pressure [bar].	3,20
Section width (mm)	645
Outer diameter of tyre [mm].	1811
Stat. radius (SLR) [mm]	823
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5514
Tread depth (mm)	30,5
Number of lugs	30x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A8	6900	40		3,20	
170 D	6000	65		3,20	