Bohnenkamp Moving Professionals

18.05.2025

TYRES

Product group	Tyres
Item number	15776010
Valid tyre size	7.00 R 12
LI / SI / PR	136 A5
TL/TT	TL
Brand	ВКТ
Tread pattern	Liftmax LM 81



Notes and features

- The BKT Liftmax LM 81 is a newly-developed industrial radial tyre produced according to the latest technology for heavy forklifts and terminal tractors.
- The strong all-steel carcass and reinforced sidewall provide excellent stability and handling in lift mode.
- Its aggressive and robust tread pattern and rubber compound provide excellent traction and a long service life.
- The radial carcass absorbs unevenness of the surface, thereby increasing driving comfort and safety of the operator and preventing fatigue.
- All Liftmax LM 81 are designed to dissipate static charge from the vehicle.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15776010
EAN	8903094044979
Valid tyre size	7.00 R 12
LI / SI / PR	136 A5
TL/TT	TL
Brand	ВКТ
Tread pattern	Liftmax LM 81
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	27,71
Recommended rim size	5.00S
Maximum air pressure [bar].	10,00
Section width (mm)	195
Outer diameter of tyre [mm].	675
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A5	2240	25	Steering wheel	10,00	
	2910	25	Load wheel	10,00	