

TYRES

Product group	Tyres
Item number	15785579
Valid tyre size	18.00 R 33
LI / SI / PR	191 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 45



Notes and features

- Multi-layer steel belt for efficient protection from puncture damage
- Deep tread pattern for very good traction

- The extra-rugged casing and a special, cut-resistant rubber compound guarantee a long service life
- Important: Mounting only permitted on multi-part rim.



Technical Informations

Item number	15785579
EAN	8903094041855
Valid tyre size	18.00 R 33
LI / SI / PR	191 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 45
TRA Code	E4
Star Rating	**
Carcass properties	H.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	465,82
Recommended rim size	13.00/2.5
Maximum air pressure [bar].	7,00
Section width (mm)	505
Outer diameter of tyre [mm].	1870
Stat. radius (SLR) [mm]	856
Rolling circumference [mm].	5608
Tread depth (mm)	55,0
Tyre capacity 75% [ltr.]	459.75
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
191 B	10900	50		7,00	