## Bohnenkamp Moving Professionals

14.03.2025

### TYRES

| Product group   | Tyres           |  |
|-----------------|-----------------|--|
| Item number     | 18315255        |  |
| Valid tyre size | 750 / 60 R 30.5 |  |
| LI / SI / PR    | 181 D           |  |
| TL/TT           | TL              |  |
| Brand           | Tianli          |  |
| Tread pattern   | Agro Grip       |  |



#### Notes and features

- The Tianli Agro Grip is a flotation tyre for on-road and offroad use.
- In field applications, the tyre offers good self-cleaning and low soil compaction.
- Used on paved roads, the Agro Grip guarantees low rolling resistance, ride comfort and fuel efficiency.
- In the version with steel belts, the tyre can also be used on construction sites.

# Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 18315255        |
|------------------------------|-----------------|
| EAN                          | 4260399945726   |
| Valid tyre size              | 750 / 60 R 30.5 |
| LI / SI / PR                 | 181 D           |
| TL/TT                        | TL              |
| Brand                        | Tianli          |
| Tread pattern                | Agro Grip       |
| Carcass properties           | Steel Belted    |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 106         |
| Nettogewicht [kg] (gültig)   | 234,00          |
| Recommended rim size         | 24.00           |
| Maximum air pressure [bar].  | 4,00            |
| Section width (mm)           | 767             |
| Outer diameter of tyre [mm]. | 1658            |
| Stat. radius (SLR) [mm]      | 735             |
| Rolling circumference [mm].  | 4986            |
| Tread depth (mm)             | 25,0            |
| E-Ready                      | No              |

#### Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 181 D | 8250               | 65           |               | 4,00                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.