

TYRES

Product group	Tyres
Item number	19800289
Valid tyre size	31 x 15.5 - 15
LI / SI / PR	124 B, 12 PR
TL/TT	TL
Brand	MRL
Tread pattern	MTR 600



Notes and features

- The MRL MTR 600 is a tyre for smaller tractors and agricultural trailers.
- Its flat, agricultural tread pattern and large contact area provide high traction on dry and wet surfaces.
- The tyre is also very suitable for tillage implements, trenchers and lawn maintenance applications.

Technical Informations

Item number	19800289
EAN	8907375025596
Valid tyre size	31 x 15.5 - 15
LI / SI / PR	124 B, 12 PR
TL/TT	TL
Brand	MRL
Tread pattern	MTR 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,75
Recommended rim size	13LB
Maximum air pressure [bar].	5,20
Section width (mm)	360
Outer diameter of tyre [mm].	790
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2300
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 B	1600	50		5,20	