

TYRES

Product group	Tyres	
Item number	19811107	
Valid tyre size	500/50-17	
LI / SI / PR	155 A8 / 142 A8, 18 PR	
TL/TT	TL	
Brand	Starco	
Tread pattern	SG Flotation	





Notes and features

- The Starco SG Flotation is a bias flotation tyre for agricultural trailers.
- Its large contact area and low inflation pressure ensure low soil compaction.
- The tyre provides good traction on soft soils and grasslands.
- Its flotation tread pattern has good self-cleaning properties.



Technical Informations

Item number	19811107
EAN	5707562459028
Valid tyre size	500/50-17
LI / SI / PR	155 A8 / 142 A8, 18 PR
TL/TT	TL
Brand	Starco
Tread pattern	SG Flotation
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,10
Recommended rim size	16
Maximum air pressure [bar].	3,70
Section width (mm)	503
Outer diameter of tyre [mm].	918
Stat. radius (SLR) [mm]	411
Rolling circumference [mm].	2842
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40	Free Rolling	3,70	
142 A8	2650	40	Drive Wheel	3,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.