

RIMS

Product group	Rims
Item number	30060110
Valid rim size	7.50 x 22.5
Rim connection	8/221/275
Bolt hole design	B2
Offset (mm)	+140
Half centre distance (HMA) [mm]	153
Rim colour	Silver
Brand	Jantsa



Technical Informations	
Load capacity of rim 1 [kg]	3400
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Nettogewicht [kg] (gültig)	36,40
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No