Bohnenkamp Moving Professionals

14.03.2025

RIMS

Product group	Rims
Item number	30820102
Valid rim size	5 JA x 12
Rim connection	5/67/112
Bolt hole design	B1
Offset (mm)	+40
Rim colour	Silver
Brand	Fira



Technical Informations

Load capacity of rim 1 [kg]	990
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	7,49
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 DS 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No