

RIMS

Product group	Rims
Item number	31459992
Valid rim size	6.00 x 17.5 H
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+114
Half centre distance (HMA) [mm]	125
Rim colour	Silver
Brand	Accuride



Technical Informations

Load capacity of rim 1 [kg]	1550
Speed Rims 1 [km/h]	130
Load capacity of rim 2 [kg]	1450
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	19,50
Hump	H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Disc thickness [mm]	11
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	BHC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21
Countersinking	Sphere
Spherical countersink [mm].	R12
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45