

## RIMS

Product group	Rims
Item number	31459995
Valid rim size	6.00 x 17.5
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+116
Half centre distance (HMA) [mm]	125
Rim colour	Silver
Brand	Accuride



## Technical Informations

Load capacity of rim 1 [kg]	1550
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	20,80
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No

---

Ventilation holes	No
Rim centering	BHC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve designation ETRTO	V3.20.5
Valve length [mm]	68.0
Valve angle [°]	27