

RIMS

Product group	Rims
Item number	31612124
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-40
Rim colour	Silver
Brand	Gianetti FAD



Technical Informations

Load capacity of rim 1 [kg]	1950
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	1850
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	2100
Speed Rims 3 [km/h]	20
Load capacity of rim 4 [kg]	2300
Speed of wheels 4 [km/h].	10
Maximum speed [km/h].	65
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	21,70

Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No