Bohnenkamp Moving Professionals

13.03.2025

RIMS

Product group	Rims
Item number	32010324
Valid rim size	13 LB X 15 H2
Rim connection	5/66.6/112
Bolt hole design	A1
Offset (mm)	-50
Rim colour	Silver
Brand	Gianetti FAD



Technical Informations

Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	1500
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Nettogewicht [kg] (gültig)	19,90
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Cavity Sealed	No
Disc thickness [mm]	8
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
Bolt hole diameter [mm]	18.5
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No