

RIMS

Product group	Rims
Item number	32013703
Valid rim size	DW 12 x 50
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+35
Rim colour	Silver
Brand	Moveero



Technical Informations

Load capacity of rim 1 [kg]	5900
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5700
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	226,00
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel

RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No