

RIMS

Product group	Rims
Item number	33060462
Valid rim size	AG 24.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	9200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6800
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	6000
Speed Rims 3 [km/h]	70
Maximum speed [km/h].	70
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	72,50
Hump	H2
Valve protection	VSH

Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No