

RIMS

Product group	Rims
Item number	33060551
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	10200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	7500
Speed Rims 2 [km/h]	65
Load capacity of rim 3 [kg]	11850
Speed Rims 3 [km/h]	25
Maximum speed [km/h].	65
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	85,00
Hump	H2
Valve protection	VSH

Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No