

RIMS

Product group	Rims
Item number	33060710
Valid rim size	AG 20.00 x 30.5 H2
Rim connection	12/371/425
Bolt hole design	A3
Offset (mm)	-10
Rim colour	Anthrazit
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	11250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	8250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	118,00
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel

RAL	RAL7016
Cavity Sealed	No
Hornverstärkung	flange reinforcement Ø16 mm
Knurling	with knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	12
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	371
Bolt hole circle diameter [mm]	425
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No