Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	39920407
Valid rim size	10 LB x 15
Rim connection	5/94/140
Offset (mm)	-50
Rim colour	Silver
Brand	Diverse

Technical Informations

Nettogewicht [kg] (gültig)	10,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No
Number of bolt holes	5
Bolt hole diameter [mm]	15
hub hole diameter [mm].	94

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Bolt hole circle diameter [mm]	140
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.