

RIMS

Product group	Rims
Item number	39920433
Valid rim size	13 x 15
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Brand	Jantasa



Allgemeine Produktabbildung. Artikel kann abweichen



Technical Informations

Load capacity of rim 1 [kg]	2800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2350
Speed Rims 2 [km/h]	50
Load capacity of rim 3 [kg]	3900
Speed Rims 3 [km/h]	10
Load capacity of rim 4 [kg]	3300
Speed of wheels 4 [km/h].	25
Maximum speed [km/h].	50
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	19,00

Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No