

WHEELS

Product group	Wheels
Item number	59696292
Valid wheel size	6.00 - 9
Brand	Deli
Tread pattern	S-252
Valid rim size	4.00 E x 9
Rim connection	5/67/112
Bolt hole design	A1
Rim colour	Silver
Load capacity complete wheel [kg]	800
Speed complete wheel [km/h]	20
Nettogewicht [kg] (gültig)	9,52
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19110161
LI / SI / PR	95 M, 10 PR
Load capacity 1 [kg]	690
Speed 1 [km/h].	130
Maximum air pressure [bar].	7,00
TL/TT	TT
Tyre colour	Black
E-Ready	No
Antistatic	No

ECE regulation number	ECE 54
Section width (mm)	163
Stat. radius (SLR) [mm]	240
Rolling circumference [mm].	1610
Tread depth (mm)	7,3
Assembly Item no. Rim	• 39600374
Speed Rims 1 [km/h]	20
Maximum speed [km/h].	20
Type of drive	Towed axle
Number of bolt holes	5
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Bolt hole design EUWA	B14 ES 28
Countersinking	Sphere
Spherical countersink [mm].	R14
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Preassembled valve	No
TPMS-kompatibles Ventil	No

Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve length [mm]	38
Valve angle [°]	gerade
Valve cap Material	Plastic
Colour of cap	Black