

WHEELS

Product group	Wheels
Item number	59696580
Valid wheel size	185 R 14 C
Brand	GT Radial
Tread pattern	KargoMax ST 6000
Valid rim size	5.5 J x 14 H2
Rim connection	4/57/100
Bolt hole design	E16
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	140
Nettogewicht [kg] (gültig)	19,40
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19866023
LI / SI / PR	104 / 102 N
Load capacity 1 [kg]	900
Speed 1 [km/h].	140
Load capacity 3 [kg]	850
Speed 3 [km/h].	140
Maximum air pressure [bar].	4,50
TL/TT	TL

M+S	M+S
Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 54 ECE 117
Rolling resistance	C
Wet grip	C
Rolling noise [db].	70
Rolling noise level	B
Section width (mm)	188
Stat. radius (SLR) [mm]	293
Rolling circumference [mm].	1983
Assembly Item no. Rim	• 39600671
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Type of drive	Towed axle
Number of bolt holes	4
hub hole diameter [mm].	57
Bolt hole circle diameter [mm]	100
Bolt hole diameter [mm]	15.5
Countersinking	Cone
Countersinking of the cone [°].	C60
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve

Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200650
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade