

WHEELS

| | |
|-----------------------------------|----------------|
| Product group | Wheels |
| Item number | 59910072 |
| Valid wheel size | 23 x 8.50 - 12 |
| Brand | BKT |
| Tread pattern | Skid Power HD |
| Valid rim size | 7.00 x 12 |
| Rim connection | 5/94/140 |
| Bolt hole design | E1 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 750 |
| Speed complete wheel [km/h] | 40 |
| Nettogewicht [kg] (gültig) | 21,25 |
| RDA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|--------------|
| Assembly Item no. Tyres | • 15772046 |
| LI / SI / PR | 98 A8, 12 PR |
| Load capacity 1 [kg] | 750 |
| Speed 1 [km/h]. | 40 |
| Maximum air pressure [bar]. | 6,20 |
| TL/TT | TL |
| Tyre colour | Black |
| E-Ready | No |
| Antistatic | No |

| | |
|--------------------------------|----------------|
| ECE regulation number | ECE 106 |
| Section width (mm) | 215 |
| Stat. radius (SLR) [mm] | 271 |
| Rolling circumference [mm]. | 1764 |
| Tread depth (mm) | 14,5 |
| Assembly Item no. Rim | • 30810265 |
| Load capacity of rim 1 [kg] | 1330 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 500 |
| Speed Rims 2 [km/h] | 80 |
| Maximum speed [km/h]. | 40 |
| Type of drive | Towed axle |
| Number of bolt holes | 5 |
| hub hole diameter [mm]. | 94 |
| Bolt hole circle diameter [mm] | 140 |
| Bolt hole diameter [mm] | 18.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R14 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL9006 |
| Valve seat | External Valve |
| Ventilation holes | No |
| Single / multi-part | einteilig |
| Hump | kein Hump |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |

| | |
|--------------------------|-------------|
| Assembly Item no. Valve | • 47201035 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 15.7 |
| Valve design | Metal valve |
| Valve designation ETRTO | V3.21.1 |
| Valve length [mm] | 33.0 |
| Valve angle [°] | gerade |